



FLOOD LIGHT LED IP65/66

Features:

High efficiency, high quality and highly reliable LED flood light fitting range. The fittings are suitable for a wide variety of applications: wall mounted around building facades, ideal for the classic floodlighting of inside and outside walkways, smaller car parks, site entrances and roads. Full circuit efficiency up to 130 Lm/Watt. CRI ≥80
Lifetime to 50,000 hours

Construction

Robust aluminium die-cast. Bracket has determined fixed angle positions that cant slip.
Tempered glass cover, high impact resistance

Range

IP65 range

- 20W 2000 lumens
- 30W 3000 lumens
- 50W 6000 lumens

IP66 range

- 75W 10 000 lumens
- 115W 15 000 lumens
- 150W 20 000 lumens

Options:

- 3 Color temperatures: 3000K, 4000K and 6500K
- Impact protection IK07 and IK08
- Suitable for operation in ambient temp. -30°C to +50°C

Compliance to following standards:

- *Safety: EN 60598*
- *Harmonics: EN 61000-3-2*
- *RFI-suppression: EN 55015, EN 55022 A*
- *Performance: EN 60929*
- *Immunity: EN 61547*
- *LED module EN 62031*
- *LED control gear performance : EN 62384*
- *LED control gear safety : EN 61347-2-13*
- *Control gear general & safety: EN 61437-1*