



Street LED High Efficiency IP66

Features:

Street LED fitting for streets, local roads, bicycle paths, alleys, pavements, car parks and squares. dust-free design.

Impressive efficiency. Full circuit efficiency > **145 Lm/W**. CRI > 70.

To 50,000 hours lifetime

Product carries a 5 year warranty when supplied with MeanWell or Invertronics driver.

Construction

Die Cast Aluminum + PC lens + Toughened glass.

Range:

60 W 8,700 lumens

80 W 11,600 lumens

100 W 14,500 lumens

120 W 17,400 lumens

150 W 21,750 lumens

180 W 26,100 lumens

Options:

- Photocell and NEMA socket
- Beam Angle: Type I-Medium/ Type II-Short/ Type II-Medium/ Type II-Long/ Type III-Short/ Type III-Medium/ BUG
- Colour temperatures 2700K, 6500K
- Can be wall or post mounted
- Lightning Protection 10KV and light sensor

Compliance to following standards:

- *Safety: EN 60598*
- *Harmonics: EN 61000-3-2*
- *RFI-suppression: EN 55015, EN 55022 A*
- *Performance: EN 60929*
- *Immunity: EN 61547*
- *LED module EN 62031*
- *LED control gear performance : EN 62384*
- *LED control gear safety : EN 61347-2-13*
- *Control gear general & safety: EN 61437-1*